



Early Journal Content on JSTOR, Free to Anyone in the World

This article is one of nearly 500,000 scholarly works digitized and made freely available to everyone in the world by JSTOR.

Known as the Early Journal Content, this set of works include research articles, news, letters, and other writings published in more than 200 of the oldest leading academic journals. The works date from the mid-seventeenth to the early twentieth centuries.

We encourage people to read and share the Early Journal Content openly and to tell others that this resource exists. People may post this content online or redistribute in any way for non-commercial purposes.

Read more about Early Journal Content at <http://about.jstor.org/participate-jstor/individuals/early-journal-content>.

JSTOR is a digital library of academic journals, books, and primary source objects. JSTOR helps people discover, use, and build upon a wide range of content through a powerful research and teaching platform, and preserves this content for future generations. JSTOR is part of ITHAKA, a not-for-profit organization that also includes Ithaka S+R and Portico. For more information about JSTOR, please contact support@jstor.org.

No. II.

PRESERVING IRON FROM RUST.

The Thanks of the Society were voted to Mr. E. WHITESIDES, of No. 14 Bateman's Buildings, Soho, for his Method of Preserving Iron from Rust.

14 Bateman's Buildings, Soho,

SIR,

February 9, 1841.

I HAVE sent you a method of preserving iron from rust, which I am desirous of laying before the Society.

I am, Sir, &c. &c.

*To the Secretary of the
Society of Arts.*

E. WHITESIDES.

The method adopted by Mr. Whitesides of preserving iron from rust may be explained in a few words. The iron is heated to redness, just perceptible in the dark, and then quenched in tallow.

In order to test the value of Mr. Whitesides' method, Mr. Binyon undertook to make experiments with iron hinges, one of which had been prepared according to Mr. Whiteside's plan, and fixed on a door of Mr. Binyon's premises, within twenty inches of the tiling, and when examined two months after being fixed, appeared to be tolerably clean, whereas an unprepared hinge, fixed at thirty-six inches from the top of the door, after the same lapse of time was considerably rusted. A third hinge, which had been prepared by Mr. Whitesides' process, was fixed at twenty inches from the ground, and was found, at the expiration of two months, to be less free

from rust than that near the roof, but considerably cleaner than the unprepared hinge.

It is to be observed, that little rain had fallen during the time of trial.

No. III.

TITANIUM FOUND IN THE BUTTERLEY
IRON-WORKS.

The Thanks of the Society were voted to JOSEPH GLYNN, Esq. F.R.S. for his Communication on Titanium found in the Blast-furnaces at the Butterley Iron-works; Specimens of which have been placed in the Society's Repository.

*Butterley Iron-Works, by Alferton,
Derbyshire, March 2, 1842.*

SIR,

I SEND you herewith some specimens of Titanium mixed with iron, which were found in the hearth or bottom of a blast-furnace belonging to the Butterley Company, which was lately blown out, that is to say, extinguished for repairing. The hearth or cavity at the bottom of the furnace is composed of large blocks of grit-stone, of nearly pure silex, of small grain, which are found partially vitrified and rent in pieces by the heat to which they have been exposed.

The Butterley Company have six of these furnaces; they are about forty feet in height, fifteen feet inside diameter at the largest part, and each furnace produces weekly from seventy to eighty tons of best melting iron, or "No. 1 Pig."

The quantity of iron-stone is nearly three tons for